

Ordering Guidelines



MG 06 M 28-11 S X B051 FR A30 003E C&C

Series - MG / MGR	
Reverse Bayonet Coupling Series (As per JSS 50815, eq. to VG 95234) [For MGR- Receptacle with Wear Pin, Plug with Spring & Friction Ring]	

Shell Style	
00	Receptacle with rear Thread
01	Cable extension receptacle with rear Thread
02	Box Mounting receptacle
06	Straight cable connector
07	Jam Nut Receptacle
08	90° Cable connector
TBF	Thru - Bulkhead receptacle

Environmental Class	
EA	backshell for Flex Tube
F	Applies to Cable plug 06, 08; Receptacle 00, 01. Scope is Cable Clamp, Telescopic Bushing & Grommet
FL	Long Coupling Nut on Plug 06
G	Backshell Type G as per VG95234 for Heat Shrink Boot
M	Backshell Type M as per VG95234 for Shielded Cable & Heat Shrink Boot
R	Environmental resistant applies to receptacle 02 (For style 00, 01 & 06 - Scope short Endbell with grommet)
T	Connector with Accessory Thread (Less Backshell & grommet) Also refer as - 211
VR	For Plug 06 & 08 - Over moulded Coupling Ring (Available in - 18, 22, 28, 36)
Y	Receptacle with PCB Contacts

Shell Size & Contact arrangement

Contact : P - Pin, S - Socket

Insert Orientation
W, X, Y, Z (as applicable)

Accessories	
C&C	Cap & Chain Assembly
SQG	SQ. Gasket for Front mounting Receptacle
SQGB	SQ. Gasket for Rear mounting Receptacle
(Size)-A or (Size)-C	3057A or 3057C Type Cable Clamp For EA type & 08R Type
ADP P(Size)+G	For PG adapter with gland*
ADP M(Size)+G	For Metric adapter with gland*
*Omit G for No Gland	
DC	Dust Cap

Finish Options	
003E	Black Zn - Co. Plated
101E	Green Zn - Co. Plated
NI	Bright nickel Plated
SS	Stainless Steel Connector
Omit for Std. Cadmium Olive Drab	

Contact Options	
A30	Crimp Contact Silver Plating
C30	Crimp Contact Gold Plating
LC	Less Contact
Omit if Std. Solder (Silver Plated)	
Contact Termination size options available (consult factory)	

Insulator Options	
FR	Flame Retardant - Elastomer Halogen free
SI	Silicon Insulator
VTN	Flouro Carbon Insulator
Omit for Std. (Polychloroprene)	

Modifications	
B05	Receptacle for rear mounting
B051	Receptacle for rear mounting with Metric Thrd. mtng. holes
B052	Receptacle for rear mounting with UN Thrd. mtng. holes
Further available - Please consult Factory	

Allied Electronics Corporation

12-D, Vikas Centre, 106, S.V.Road,
Santacruz (West), Mumbai - 400 054, India

Website : www.aeconnectors.com

E-mail : alliedho@aeconnectors.com, sales@aeconnectors.com
Tel : +91 22 61953636; 61953608, Fax : +91 22 61953699

" Connect Through Allied "