

# Metric Range Ordering Guidelines

Type : 2RM, 2RMD



2RM G 18 K P E 7 G 1 V 1 B BK  
2PM (Γ) 18 K (Π) (Ξ) 7 (Γ) 1 B 1 (B) - ----- (Original part reference)

Series	
2RM Series (2PM)	
2RMD Series (2PM A)	

G	Sealed Connector
Applicable only for receptacle	

Shell size	
14, 18, 22, 24, 27, 30, 33, 36, 39, 42 & 45	

Shell type	
B	Receptacle
K	Plug

Backshell	
P	Straight Backshell
U	Angular Backshell

Cable termination	
E	Screen end nut
N	Cable clamp

Number of Contacts	
--------------------	--

Insulator material	
Glass filled phenolic insulator	
Omit for Std. Polychloroprene (Neoprene)	

Rear accessory	
B	Receptacle connector type without thread
L	Left socket ( Mating plug of bulkhead conector )

Operating temperature	
55° C to + 125° C ( JSS 50860 )	

Contact Plating	
V	Silver
A	Gold ( flash )

Symbolic number of Contact Set	
--------------------------------	--

Type of Contact	
G	Female (socket) contact
SH	Male (pin) contact

**Allied Electronics Corporation**

12-D, Vikas Centre, 106, S.V.Road,  
Santacruz ( West ), Mumbai - 400 054, India

Website : [www.aeccconnectors.com](http://www.aeccconnectors.com)

E-mail : [alliedho@aeccconnectors.com](mailto:alliedho@aeccconnectors.com), [sales@aeccconnectors.com](mailto:sales@aeccconnectors.com)  
Tel : +91 22 61953636; 61953608, Fax : +91 22 61953699

" Connect Through Allied "